SDS Revision Date: 04/20/2015 File No.: 0053

# 1. Identification

1.1. Product identifier

Product Identity

Life Calk Type "H" Part A (Black)

Alternate Names

Life Calk Type "H" Part A (Black)

Polysulfide Sealant Polysulfide Caulk

Product Codes: 1047, 1048

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Deck Sealant, Bedding Compound, General Sealant

1.3. Details of the supplier of the safety data sheet

Company Name Life Industries Corporation

4060 Bridge View Drive N. Charleston, SC 29405

**Emergency** 

**CHEMTREC (USA)** (800) 424-9300

**24 hour Emergency Telephone No.** USA: 1-800-424-9300

Outside USA: +1-703-527-3887

Customer Service: Life Industries Corporation +1-843-566-1225

# 2. Hazard(s) identification

#### 2.1. Classification of the substance or mixture

Skin Irrit. 3;H316 Causes mild skin irritation. (Not adopted by US OSHA)

Repr. 2;H361D Suspected of damaging the unborn child.

STOT RE 2:H373 May cause damage to organs through prolonged or repeated exposure. Specific Target

Organs: (Not Available)

#### 2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



SDS Revision Date: 04/20/2015 File No.: 0053

H316 Causes mild skin irritation.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

#### [Prevention]:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe mist / vapors / spray.

P281 Use personal protective equipment as required.

# [Response]:

P308+313 IF exposed or concerned: Get medical advice / attention.

P314 Get Medical advice / attention if you feel unwell.

P332+313 If skin irritation occurs: Get medical advice / attention.

## [Storage]:

P405 Store locked up.

# [Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

# 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Toluene CAS Number: 0000108-88-3	1.0 - 10	Flam. Liq. 2;H225 Repr. 2;H361d Asp. Tox. 1;H304 STOT RE 2;H373 Skin Irrit. 2;H315 STOT SE 3;H336	[1][2]

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

- [1] Substance classified with a health or environmental hazard.
- [2] Substance with a workplace exposure limit.
- [3] PBT-substance or vPvB-substance.

# 4. First aid measures

<sup>\*</sup>The full texts of the phrases are shown in Section 16.

04/20/2015 **SDS Revision Date:** File No.: 0053

## 4.1. Description of first aid measures

General In all cases of doubt, or when symptoms persist, seek medical attention.

Never give anything by mouth to an unconscious person.

Inhalation Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give

artificial respiration. If unconscious place in the recovery position and obtain immediate

medical attention. Give nothing by mouth.

**Eyes** Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and

seek medical attention.

Skin Remove contaminated clothing. Wash skin thoroughly with soap and water or use a

recognized skin cleanser.

Ingestion If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

#### 4.2. Most important symptoms and effects, both acute and delayed

Overview Eyes: May cause irritation.

Skin: May cause irritation.

Ingestion: Not known.

Inhalation: Inhalation is not an expect hazard unless misted or heated to high temperatures

Chronic Health Hazards: No information found.

Medical Conditions Generally Aggravated by Exposure: NA

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation

and soreness with possible reversible damage. See section 2 for further details.

Skin Causes mild skin irritation. (Not adopted by US OSHA)

# 5. Fire-fighting measures

## 5.1. Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO<sub>2</sub>, powder.

Do not use: water jet.

SDS Revision Date: 04/20/2015 File No.: 0053

## 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Sulfur oxides (Contact with water could product sulfuric acid; this is only a concern for large amounts of material engulfed in flames).

Do not breathe mist / vapors / spray.

## 5.3. Advice for fire-fighters

In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode.

Not considered to be an explosion hazard.

ERG Guide No. --

# 6. Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

## 6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

## 6.3. Methods and material for containment and cleaning up

Confine spill and place in a closed container. Wipe up excess with dry rags and place in a closed container.

# 7. Handling and storage

## 7.1. Precautions for safe handling

BE SURE TO HAVE PROPER VENTILATION TO MINIMIZE EXPOSURE TO VAPORS.

Avoid contact with skin and eyes by using personal protective equipment.

See section 2 for further details. - [Prevention]:

## 7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Incompatible materials: Strong oxidizing agents.

Product is moisture sensitive (store in a dark, DRY place).

See section 2 for further details. - [Storage]:

## 7.3. Specific end use(s)

No data available.

# 8. Exposure controls and personal protection

#### 8.1. Control parameters

SDS Revision Date: 04/20/2015 File No.: 0053

## **Exposure**

CAS No.	Ingredient	Source	Value
0000108-88-3	Toluene	OSHA	TWA 200 ppm C 300 ppm 500 ppm (10-minute maximum peak)STEL 150 ppm
		ACGIH	TWA: 20 ppmR
		NIOSH	TWA 100 ppm (375 mg/m3) ST 150 ppm (560 mg/m3)
		Supplier	No Established Limit

## Carcinogen Data

CAS No.	Ingredient	Source	Value	
0000108-88-3	Toluene	OSHA	Select Carcinogen: No	
		NTP	Known: No; Suspected: No	
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;	

## 8.2. Exposure controls

RespiratoryNot generally required.EyesGoggles should be worn.SkinPVC or rubber gloves.

**Engineering Controls** Provide adequate ventilation. Where reasonably practicable this should be achieved by the

use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits

suitable respiratory protection must be worn.

using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

# 9. Physical and chemical properties

Appearance Black Liquid
Odor Polysulfide
Odor threshold Not Measured
pH Not Measured
Melting point / freezing point Not Measured
Initial boiling point and boiling range Not Measured
Flash Point Not Measured

SDS Revision Date: 04/20/2015 File No.: 0053

Evaporation rate (Ether = 1) Not Measured Flammability (solid, gas) Not Applicable

Upper/lower flammability or explosive limits Lower Explosive Limit: Not Measured

**Upper Explosive Limit:** Not Measured

Vapor pressure (Pa) Not Measured **Vapor Density** Not Measured Specific Gravity Not Measured Solubility in Water Insoluble Partition coefficient n-octanol/water (Log Kow) Not Measured **Auto-ignition temperature** Not Measured **Decomposition temperature** Not Measured Viscosity (cSt) Not Measured

% Volatile 2%

9.2. Other information

No other relevant information.

# 10. Stability and reactivity

#### 10.1. Reactivity

Hazardous Polymerization will not occur.

# 10.2. Chemical stability

Stable under normal circumstances.

#### 10.3. Possibility of hazardous reactions

No data available.

#### 10.4. Conditions to avoid

No data available.

## 10.5. Incompatible materials

Strong oxidizing agents.

#### 10.6. Hazardous decomposition products

Sulfur oxides (Contact with water could product sulfuric acid; this is only a concern for large amounts of material engulfed in flames).

# 11. Toxicological information

#### **Acute toxicity**

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in

SDS Revision Date: 04/20/2015 File No.: 0053

dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

2-butoxyethanol and its acetate are readily absorbed through the skin and will cause harmful effects on the blood.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Toluene - (108-88-3)	636.00, Rat - Category: 4	8,400.00, Rabbit - Category: NA	No data available	No data available	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description
Acute toxicity (oral)		Not Applicable
Acute toxicity (dermal)		Not Applicable
Acute toxicity (inhalation)		Not Applicable
Skin corrosion/irritation	3	Causes mild skin irritation. (Not adopted by US OSHA)
Serious eye damage/irritation		Not Applicable
Respiratory sensitization		Not Applicable
Skin sensitization		Not Applicable
Germ cell mutagenicity		Not Applicable
Carcinogenicity		Not Applicable
Reproductive toxicity	2	Suspected of damaging the unborn child.
STOT-single exposure		Not Applicable
STOT-repeated exposure	2	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard		Not Applicable

# 12. Ecological information

## 12.1. Toxicity

Harmful to aquatic life.

# **Aquatic Ecotoxicity**

Ingredient	96 hr LC50 fish,	48 hr EC50 crustacea,	ErC50 algae,	
	mg/l	mg/l	mg/l	
Toluene - (108-88-3)	5.80, Oncorhynchus mykiss	19.60, Daphnia magna	Not Available	

04/20/2015 **SDS Revision Date:** File No.: 0053

## 12.2. Persistence and degradability

There is no data available on the preparation itself.

# 12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

#### 12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

#### 12.6. Other adverse effects

No data available.

# 13. Disposal considerations

#### 13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

# 14. Transport information

**DOT (Domestic Surface** IMO / IMDG (Ocean ICAO/IATA

**IMDG:** Not Applicable

Not Applicable

Sub Class: Not Applicable

Air Class: Not Applicable

Not Applicable

Transportation) Transportation) 14.1. UN number Not Applicable Not Regulated Not Regulated Not Regulated Not Regulated Not Regulated

14.2. UN proper shipping

14.3. Transport hazard

name

**DOT Hazard Class:** Not

class(es)

Applicable

14.4. Packing group Not Applicable

14.5. Environmental hazards

**IMDG** Marine Pollutant: No

14.6. Special precautions for user

No further information

# 15. Regulatory information

**Regulatory Overview** The regulatory data in Section 15 is not intended to be all-inclusive, only selected

regulations are represented.

**Toxic Substance** All components of this material are either listed or exempt from listing on the TSCA

Control Act (TSCA) Inventory. WHMIS Classification D2A

SDS Revision Date: 04/20/2015 File No.: 0053

US EPA Tier II Hazards Fire: No

Sudden Release of Pressure: No

Reactive: No

Immediate (Acute): Yes Delayed (Chronic): Yes

#### EPCRA 311/312 Chemicals and RQs (lbs):

Toluene (1,000.00)

## **EPCRA 302 Extremely Hazardous:**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

#### **EPCRA 313 Toxic Chemicals:**

Toluene

## Proposition 65 - Carcinogens (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

## Proposition 65 - Developmental Toxins (>0.0%):

Toluene

## Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

## Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

#### **New Jersey RTK Substances (>1%):**

Toluene

#### Pennsylvania RTK Substances (>1%):

Toluene

# 16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapor.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness and dizziness.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

SDS Revision Date: 04/20/2015 File No.: 0053

This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.

DISCLAIMER: The information and recommendations contained herein are based upon data believed to be correct. Life Industries Corporation assumes no liability for misinterpretation of the data contained within this form as any type of warranty or guarantee of the product.

**End of Document**