SDS Revision Date: 05/02/2019 File No.: 0001

1. Identification

1.1. Product identifier

Product Identity

Alternate Names

Life Calk (White)

Polysulfide Sealant

Polysulfide Caulk

Product Codes: 1305, 1030, 1033, 1372, 12033, LI1030

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Deck Sealant, Bedding Compound, General Sealant

Application Method See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name Life Industries Corporation

4060 Bridge View Drive N. Charleston, SC 29405

Emergency

CHEMTREC (USA) (800) 424-9300

24 hour Emergency Telephone No. USA: 1-800-424-9300

Outside USA: +1-703-527-3887

Customer Service: Life Industries Corporation +1-843-566-1225

2. Hazard(s) identification

2.1. Classification of the substance or mixture

Repr. 2;H361D Suspected of damaging the unborn child.

STOT RE 2;H373 May cause damage to organs through prolonged or repeated exposure. Specific Target

Organs: (Not Available)

2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



H361d Suspected of damaging the unborn child.

SDS Revision Date: 05/02/2019 File No.: 0001

H373 May cause damage to organs through prolonged or repeated exposure.

[Prevention]:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe mist / vapors / spray.

P281 Use personal protective equipment as required.

[Response]:

P308+313 IF exposed or concerned: Get medical advice / attention.

P314 Get Medical advice / attention if you feel unwell.

[Storage]:

P405 Store locked up.

[Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Calcium peroxide (Ca(O2)) CAS Number: 0001305-79-9	1.0 - 10	Ox. Sol. 2;H272 Skin Irrit. 2;H315 Eye Irrit. 2;H319 STOT SE 3;H335	[1]
Barium hydroxide (Ba(OH)2) CAS Number: 0017194-00-2	1.0 - 10	Acute Tox. 4;H302 Skin Corr. 1A;H314 Eye Dam. 1;H318	[1]
Toluene CAS Number: 0000108-88-3	1.0 - 10	Flam. Liq. 2;H225 Repr. 2;H361d Asp. Tox. 1;H304 STOT RE 2;H373 Skin Irrit. 2;H315 STOT SE 3;H336	[1][2]

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. First aid measures

4.1. Description of first aid measures

General In all cases of doubt, or when symptoms persist, seek medical attention.

Never give anything by mouth to an unconscious person.

^[1] Substance classified with a health or environmental hazard.

^[2] Substance with a workplace exposure limit.

^[3] PBT-substance or vPvB-substance.

^{*}The full texts of the phrases are shown in Section 16.

SDS Revision Date: 05/02/2019 File No.: 0001

Inhalation Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give

artificial respiration. If unconscious place in the recovery position and obtain immediate

medical attention. Give nothing by mouth.

Eyes Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and

seek medical attention.

Skin Remove contaminated clothing. Wash skin thoroughly with soap and water or use a

recognized skin cleanser.

Ingestion If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Overview Eyes: May cause irritation.

Skin: May cause irritation.

Ingestion: Not known.

Inhalation: Inhalation is not an expect hazard unless misted or heated to high temperatures

Chronic Health Hazards: No information found.

Medical Conditions Generally Aggravated by Exposure: NA

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

5. Fire-fighting measures

5.1. Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO₂, powder.

Do not use: water.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Sulfur oxides (Contact with water could product sulfuric acid; this is only a concern for large amounts of material engulfed in flames).

Do not breathe mist / vapors / spray.

5.3. Advice for fire-fighters

In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode.

Not considered to be an explosion hazard.

SDS Revision Date: 05/02/2019 File No.: 0001

None

ERG Guide No. ----

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Confine spill and place in a closed container. Wipe up excess with dry rags and place in a closed container.

7. Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes by using personal protective equipment.

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Incompatible materials: Strong oxidizing agents.

Product is moisture sensitive (store in a dark, DRY place).

See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

No data available.

8. Exposure controls and personal protection

8.1. Control parameters

Exposure

CAS No.	Ingredient	Source	Value
0000108-88-3	Toluene	OSHA	TWA 200 ppm C 300 ppm 500 ppm (10-minute maximum peak)STEL 150 ppm
		ACGIH	TWA: 20 ppmR
		NIOSH	TWA 100 ppm (375 mg/m3) ST 150 ppm (560 mg/m3)
		Supplier	No Established Limit
0001305-79-9	Calcium peroxide (Ca(O2))	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit

SDS Revision Date: 05/02/2019 File No.: 0001

		Supplier	No Established Limit
0017194-00-2	Barium hydroxide (Ba(OH)2)	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit

Carcinogen Data

CAS No.	Ingredient	Source	Value
0000108-88-3	Toluene	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0001305-79-9	Calcium peroxide (Ca(O2))	OSHA Select Carcinogen: No	
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0017194-00-2	Barium hydroxide (Ba(OH)2)	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

8.2. Exposure controls

RespiratoryNot generally required.EyesGoggles should be worn.SkinPVC or rubber gloves.

Engineering Controls Provide adequate ventilation. Where reasonably practicable this should be achieved by the

use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits

suitable respiratory protection must be worn.

Other Work Practices Use good personal hygiene practices. Wash hands before eating, drinking, smoking or

using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

9. Physical and chemical properties

Appearance Thick White Paste

Odor Polysulfide
Odor threshold Not Measured
pH Not Measured
Melting point / freezing point Not Measured
Initial boiling point and boiling range Not Measured
Flash Point Not Measured
Evaporation rate (Ether = 1) Not Measured

SDS Revision Date: 05/02/2019 File No.: 0001

Flammability (solid, gas) Not Applicable

Upper/lower flammability or explosive limits Lower Explosive Limit: Not Measured

Upper Explosive Limit: Not Measured

Vapor pressure (Pa) Not Measured **Vapor Density** Not Measured **Specific Gravity** Not Measured Solubility in Water Insoluble Partition coefficient n-octanol/water (Log Kow) Not Measured **Auto-ignition temperature** Not Measured **Decomposition temperature** Not Measured Viscosity (cSt) Not Measured

% Volatile 2%

9.2. Other information

California Product Category: Chemically Curing Sealant <3.0% VOC W/W

10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

No data available.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Sulfur oxides (Contact with water could product sulfuric acid; this is only a concern for large amounts of material engulfed in flames).

11. Toxicological information

Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

SDS Revision Date: 05/02/2019 File No.: 0001

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Calcium peroxide (Ca(O2)) - (1305-79-9)	No data available	No data available	No data available	No data available	No data available
Barium hydroxide (Ba(OH)2) - (17194-00-2)	No data available	No data available	No data available	No data available	No data available
Toluene - (108-88-3)	636.00, Rat - Category: 4	8,400.00, Rabbit - Category: NA	No data available	No data available	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description	
Acute toxicity (oral)		Not Applicable	
Acute toxicity (dermal)		Not Applicable	
Acute toxicity (inhalation)		Not Applicable	
Skin corrosion/irritation		Not Applicable	
Serious eye damage/irritation		Not Applicable	
Respiratory sensitization		Not Applicable	
Skin sensitization		Not Applicable	
Germ cell mutagenicity		Not Applicable	
Carcinogenicity		Not Applicable	
Reproductive toxicity	2	Suspected of damaging the unborn child.	
STOT-single exposure		Not Applicable	
STOT-repeated exposure	2	May cause damage to organs through prolonged or repeated exposure.	
Aspiration hazard		Not Applicable	

12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish,	48 hr EC50 crustacea,	ErC50 algae,
	mg/l	mg/l	mg/l
Calcium peroxide (Ca(O2)) - (1305-79-9)	Not Available	Not Available	Not Available

File No.: 0001 **SDS Revision Date:** 05/02/2019

Barium hydroxide (Ba(OH)2) - (17194-00-2)	Not Available	Not Available	Not Available
Toluene - (108-88-3)	5.80, Oncorhynchus mykiss	19.60, Daphnia magna	Not Available

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.

13. Disposal considerations

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

14. Transport information

DOT (Domestic Surface ICAO/IATA IMO / IMDG (Ocean **Transportation**) Transportation)

14.1. **UN** number Not Applicable Not Regulated Not Regulated

14.2. UN proper shipping Not Regulated Not Regulated Not Regulated name

14.3. Transport hazard **DOT Hazard Class:** Not **IMDG:** Not Applicable Air Class: Not Applicable

class(es) **Applicable** Sub Class: Not Applicable 14.4. Packing group Not Applicable Not Applicable Not Applicable

14.5. Environmental hazards

IMDG Marine Pollutant: No

14.6. Special precautions for user

No further information

15. Regulatory information

The regulatory data in Section 15 is not intended to be all-inclusive, only selected Regulatory Overview

regulations are represented.

SDS Revision Date: 05/02/2019 File No.: 0001

Toxic Substance All components of this material are either listed or exempt from listing on the TSCA

Control Act (TSCA) Inventory.

WHMIS Classification D2A

US EPA Tier II Hazards Fire: No

Sudden Release of Pressure: No

Immediate (Acute): No
Delayed (Chronic): Yes

Reactive: No

EPCRA 311/312 Chemicals and RQs (lbs):

Toluene (1,000.00)

EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 Toxic Chemicals:

Toluene

Proposition 65 - Carcinogens (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Developmental Toxins (>0.0%):

Toluene

Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

New Jersey RTK Substances (>1%):

Calcium peroxide (Ca(O2))

Toluene

Pennsylvania RTK Substances (>1%):

Toluene

California CARB Category:

Chemically Curing Sealant <3.0% VOC W/W

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

SDS Revision Date: 05/02/2019 File No.: 0001

H225 Highly flammable liquid and vapor.

H272 May intensify fire; oxidizer.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness and dizziness.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.

DISCLAIMER: The information and recommendations contained herein are based upon data believed to be correct. Life Industries Corporation assumes no liability for misinterpretation of the data contained within this form as any type of warranty or guarantee of the product.

End of Document