

Safety Data Sheet

Life Calk (White)

SDS Revision Date:

05/04/2015 File No.: 0001

1. Identification

1.1. Product identifier

Product Identity Life Calk (White)
Alternate Names Life Calk (White)
Polysulfide Sealant
Polysulfide Caulk
Product Codes: 1305, 1030, 1033, 1372

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Deck Sealant, Bedding Compound, General Sealant
Application Method See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name Life Industries Corporation
4060 Bridge View Drive
N. Charleston, SC 29405

Emergency
CHEMTREC (USA) (800) 424-9300
24 hour Emergency Telephone No. USA: 1-800-424-9300
Outside USA: +1-703-527-3887
Customer Service: Life Industries Corporation +1-843-566-1225

2. Hazard(s) identification

2.1. Classification of the substance or mixture

Repr. 2;H361D Suspected of damaging the unborn child.
STOT RE 2;H373 May cause damage to organs through prolonged or repeated exposure. Specific Target Organs: (Not Available)

2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.

Safety Data Sheet

Life Calk (White)

SDS Revision Date:

05/04/2015 File No.: 0001



Warning

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

[Prevention]:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe mist / vapors / spray.

P281 Use personal protective equipment as required.

[Response]:

P308+313 IF exposed or concerned: Get medical advice / attention.

P314 Get Medical advice / attention if you feel unwell.

[Storage]:

P405 Store locked up.

[Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Calcium peroxide (Ca(O ₂)) CAS Number: 0001305-79-9	1.0 - 10	Ox. Sol. 2;H272 Skin Irrit. 2;H315 Eye Irrit. 2;H319 STOT SE 3;H335	[1]
Barium hydroxide (Ba(OH) ₂) CAS Number: 0017194-00-2	1.0 - 10	Acute Tox. 4;H302 Skin Corr. 1A;H314 Eye Dam. 1;H318	[1]
Toluene CAS Number: 0000108-88-3	1.0 - 10	Flam. Liq. 2;H225 Repr. 2;H361d Asp. Tox. 1;H304 STOT RE 2;H373 Skin Irrit. 2;H315 STOT SE 3;H336	[1][2]

Safety Data Sheet

Life Calk (White)

SDS Revision Date:

05/04/2015 File No.: 0001

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

4. First aid measures

4.1. Description of first aid measures

General	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
Eyes	Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
Skin	Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
Ingestion	If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Overview	Eyes: May cause irritation. Skin: May cause irritation. Ingestion: Not known. Inhalation: Inhalation is not an expect hazard unless misted or heated to high temperatures Chronic Health Hazards: No information found. Medical Conditions Generally Aggravated by Exposure: NA Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.
-----------------	---

Safety Data Sheet

Life Calk (White)

SDS Revision Date:

05/04/2015 File No.: 0001

5. Fire-fighting measures

5.1. Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO₂, powder.

Do not use: water.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Sulfur oxides (Contact with water could product sulfuric acid; this is only a concern for large amounts of material engulfed in flames).

Do not breathe mist / vapors / spray.

5.3. Advice for fire-fighters

In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode.

Not considered to be an explosion hazard.

None

ERG Guide No. ----

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Confine spill and place in a closed container. Wipe up excess with dry rags and place in a closed container.

7. Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes by using personal protective equipment.

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Incompatible materials: Strong oxidizing agents.

Product is moisture sensitive (store in a dark, DRY place).

See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

Safety Data Sheet

Life Calk (White)

SDS Revision Date:

05/04/2015 File No.: 0001

No data available.

8. Exposure controls and personal protection

8.1. Control parameters

Exposure

CAS No.	Ingredient	Source	Value
0000108-88-3	Toluene	OSHA	TWA 200 ppm C 300 ppm 500 ppm (10-minute maximum peak)STEL 150 ppm
		ACGIH	TWA: 20 ppmR
		NIOSH	TWA 100 ppm (375 mg/m3) ST 150 ppm (560 mg/m3)
		Supplier	No Established Limit
0001305-79-9	Calcium peroxide (Ca(O ₂))	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0017194-00-2	Barium hydroxide (Ba(OH) ₂)	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit

Carcinogen Data

CAS No.	Ingredient	Source	Value
0000108-88-3	Toluene	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0001305-79-9	Calcium peroxide (Ca(O ₂))	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0017194-00-2	Barium hydroxide (Ba(OH) ₂)	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

8.2. Exposure controls

Respiratory Not generally required.

Eyes Goggles should be worn.

Skin PVC or rubber gloves.

Safety Data Sheet

Life Calk (White)

SDS Revision Date:

05/04/2015 File No.: 0001

Engineering Controls Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.

Other Work Practices Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

9. Physical and chemical properties

Appearance	Thick White Paste
Odor	Polysulfide
Odor threshold	Not Measured
pH	Not Measured
Melting point / freezing point	Not Measured
Initial boiling point and boiling range	Not Measured
Flash Point	Not Measured
Evaporation rate (Ether = 1)	Not Measured
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: Not Measured Upper Explosive Limit: Not Measured
Vapor pressure (Pa)	Not Measured
Vapor Density	Not Measured
Specific Gravity	Not Measured
Solubility in Water	Insoluble
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	Not Measured
Decomposition temperature	Not Measured
Viscosity (cSt)	Not Measured
% Volatile	2%

9.2. Other information

No other relevant information.

10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

Safety Data Sheet

Life Calk (White)

SDS Revision Date:

05/04/2015 File No.: 0001

No data available.

10.4. Conditions to avoid

No data available.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Sulfur oxides (Contact with water could product sulfuric acid; this is only a concern for large amounts of material engulfed in flames).

11. Toxicological information

Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Calcium peroxide (Ca(O ₂)) - (1305-79-9)	No data available	No data available	No data available	No data available	No data available
Barium hydroxide (Ba(OH) ₂) - (17194-00-2)	No data available	No data available	No data available	No data available	No data available
Toluene - (108-88-3)	636.00, Rat - Category: 4	8,400.00, Rabbit - Category: NA	No data available	No data available	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	---	Not Applicable
Serious eye damage/irritation	---	Not Applicable
Respiratory sensitization	---	Not Applicable

Safety Data Sheet

Life Calk (White)

SDS Revision Date:

05/04/2015 File No.: 0001

Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	2	Suspected of damaging the unborn child.
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	2	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	---	Not Applicable

12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Calcium peroxide (Ca(O ₂)) - (1305-79-9)	Not Available	Not Available	Not Available
Barium hydroxide (Ba(OH) ₂) - (17194-00-2)	Not Available	Not Available	Not Available
Toluene - (108-88-3)	5.80, Oncorhynchus mykiss	19.60, Daphnia magna	Not Available

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.

13. Disposal considerations

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

14. Transport information

Safety Data Sheet

Life Calk (White)

SDS Revision Date:

05/04/2015 File No.: 0001

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
14.1. UN number	Not Applicable	Not Regulated	Not Regulated
14.2. UN proper shipping name	Not Regulated	Not Regulated	Not Regulated
14.3. Transport hazard class(es)	DOT Hazard Class: Not Applicable	IMDG: Not Applicable Sub Class: Not Applicable	Air Class: Not Applicable
14.4. Packing group	Not Applicable	Not Applicable	Not Applicable
14.5. Environmental hazards			
IMDG	Marine Pollutant: No		
14.6. Special precautions for user	No further information		

15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.

Toxic Substance Control Act (TSCA) All components of this material are either listed or exempt from listing on the TSCA Inventory.

WHMIS Classification D2A

US EPA Tier II Hazards

Fire: No

Sudden Release of Pressure: No

Reactive: No

Immediate (Acute): No

Delayed (Chronic): Yes

EPCRA 311/312 Chemicals and RQs (lbs):

Toluene (1,000.00)

EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 Toxic Chemicals:

Toluene

Proposition 65 - Carcinogens (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Developmental Toxins (>0.0%):

Toluene

Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

New Jersey RTK Substances (>1%):

Safety Data Sheet

Life Calk (White)

SDS Revision Date:

05/04/2015 File No.: 0001

Calcium peroxide (Ca(O₂))

Toluene

Pennsylvania RTK Substances (>1%):

Toluene

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapor.

H272 May intensify fire; oxidizer.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness and dizziness.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.

DISCLAIMER: The information and recommendations contained herein are based upon data believed to be correct. Life Industries Corporation assumes no liability for misinterpretation of the data contained within this form as any type of warranty or guarantee of the product.

End of Document